

Recommended Spare Parts
ECM-Ex2-2 WITHOUT HEAT EXCHANGER 230V Gas Cooler

Manufacturer P/N	Cemtrex P/N	Description
93K0140	20-307-2463	Jet-stream heat exchanger for cooler type ECP3000/ECM-1/ECC-1. Material: Duran glass. Connections: sample gas GL18-6mm, condensate GL25-12mm.
93K0170	20-307-2467	Jet-stream heat exchanger for cooler type ECP3000/ECM-1/ECC-1. Material: PVDF. Connections: sample gas G1/4"i, condensate G3/8"i.
93K0160	20-307-2465	Jet-stream heat exchanger for cooler type ECP3000/ECM-1/SCC-1. Material: SS316. Connections: sample gas G1/4"i, condensate G3/8"i.
93K0150	20-307-2464	Jet-stream heat exchanger for cooler type ECP3000/ECM-1/ECC-1, 90° Material: Duran glass. Connections: sample gas GL18-6/6mm, condensat : GL18-8mm.
97K0100	20-307-2486	Jet stream heat exchanger, type ECM-2G, material Duran glass, connections: sample gas GL18-6/6mm, condensate GL25-12mm.
97K0110	20-307-2487	Jet stream heat exchanger, type ECM-2PV, material PVDF, connections: sample gas 6mm condensate G3/8"i.
97K0115	20-307-2488	Jet stream heat exchanger, type ECM-2SS, material SS316, connections: sample gas 6 mm condensate G3/8"i.
90K0114	20-307-2440	Thermal conductivity paste, -20 to +140°C, silicon free, 5gr.
90K0115	20-307-2441	Thermal conductivity paste, -20 to +140°C, silicon free, 50gr.
90K0035	20-307-2489	ECP-1, EC-FD fan 230V 50Hz.
97K0010	20-307-2490	Transformator ECM 115/230V 230VA
90P1007	20-307-2398	Tube Set for peristaltic pump SR25 with PVDF tube connection 4/6mm.
90P1010	20-307-2399	1 set contact spring for driver of peristaltic pump SR25.1, (set = 4 pcs.)
90P1020	20-307-2400	Driver complete for peristaltic pump SR25.1
90P1045	20-307-2401	Contact pulley(1 pc.) for peristaltic pump SR25.1, (2 pcs./pump required).
90P1050	20-307-2402	Conveying belt for peristaltic pump SR25.1
90P1025	20-307-2492	S-bolt for peristaltic pump SR25.1
90P1030	20-307-2404	Pump head complete for peristaltic pump SR25.1, with rubberdisk, without motor and gear.

Manufacturer P/N	Centrex P/N	Description
01P1300	20-307-2491	Peristaltic pump SR25.2, for panel mounting Wall thickness max.1,5mm capacity of 0,30 l/hr, pressure range 200mbar up to 2,2bar abs. Material: Novopren, PVDF, connections for tube DN 4/6mm, power: 115/230V, 50/60Hz.
91F1010	20-307-2451	Sealing ring GL18-6mm, material: PTFE.
91F1015	20-307-2452	Sealing ring GL18-8mm, material: PTFE.
90F0025	20-307-2453	Sealing ring GL25-12mm, material: PTFE.
91F1005	20-307-2454	Spare union nut GL18.
91F1007	20-307-2455	Spare union nut GL18/14
90F0020	20-307-2456	Union nut GL25.
90F0022	20-307-2457	Union nut GL25/18.
01B8365	20-307-2495	Electron. PID-temperature controller for ECM-ExII power 230/115V 50/60 Hz.
97K0235	20-307-2496	Compressor thermoswitch Klixon 230V, ECM Zone 2, DIV II.