

Recommended Spare Parts
SP10-H Gas Sample Probe

Manufacturer P/N	Cemtrex P/N	Description
90S1005	20-307-2365	Insitu stainless steel filter type V10, without volume displacer. Filter porosity: 2µm, Length: 225mm, 46mm OD, Material: SS316.
90S1010	20-307-2366	Insitu Hastelloy filter type V10/HC, without volume displacer. Filter porosity: 2µm, Length: 225mm, 46mm OD, Material: Hastelloy-C.
90S1012	20-307-2367	Insitu Hastelloy filter type V10-0/HC, with volume displacer. Filter porosity: 2µm, Length: 225mm, 46mm OD, Material: Hastelloy-C.
90S1015	20-307-2372	Insitu stainless steel filter type V10-1, with volume displacer. Filter porosity: 2µm, Length: 550mm, 60mm OD, Material: SS316.
90S1016	20-307-2373	Insitu Hastelloy filter type V10-1/HC, with volume displacer. Filter porosity: 2µm, Length: 550mm, 60mm OD, Material: Hastelloy-C.
90S1017	20-307-2369	Insitu stainless steel filter type V10-2, without volume displacer. Filter porosity: 2µm, Length: 550mm, 60mm OD, Material: SS316.
90S1018	20-307-2370	Insitu Hastelloy filter type V10-2/HC, without volume displacer. Filter porosity: 2µm, Length: 550mm, 60mm OD, Material: Hastelloy-C.
93S0018	20-307-2340	Temperature resistant heat sink compound, 100g-tube.
90S0005	20-307-2374	Cartridge heater element for SP10/23H, SP23, Filter H/H0, L=130mm, 230VAC/315W.
90S0006	20-307-2375	Heating cartridge for SP10-H/23H, filter H/H0, L=130mm, 115VAC/200W.
90S0010	20-307-2376	Thermostat 50-320°C for SP10-H und SP20-H up to model 1986, sensor diameter 4mm.
90S2075	20-307-2324	Flange gasket set for DN65 PN6B consisting of gasket (67) and a set of screws M12x60.
93S0060	20-307-2343	Spare thermoelement Fe-CuNi for SP.../H320.
90S0013	20-307-2377	Over temperature switch setting to 220°C for SP10-H until SP30-H, Filter FT-H/H1.
90S1020	20-307-2371	Gasket 1" for SP10/11/21/31 V10.
90S2077	20-307-2322	Flange gasket DN65 PN6B (67). Material: Novapress.