

**Recommended Spare Parts**
**SP2000-H320/DIL-BR 230V Gas Sample Probe**

<b>Manufacturer P/N</b>	<b>Cemtrex P/N</b>	<b>Description</b>
90S0020	20-336-2000	Filter element type S-2K150. Length: 150mm, material: ceramics, filter porosity: 2µm.
90F0125	20-307-2314	Filter element type F-0,1GF150. Length: 150mm, material: glass fiber, filter porosity: 0,1µm.
93S2083	20-307-2315	Special spun-glass hightemperature resistant for probes with /FW insert. Contents:1000g.
20S4301	20-307-2429	Complete set SP2000H/320 DIL critical orifice incl. 4x graphitring, 1x washer Material: glass # please indicate ratio with the order.
93S2096	20-307-2316	Spun glass cartridge element FW with Demister, stainless steel, without filling.
93S0055	20-307-2336	Gasket (30) for filter element. Material: Graphite.
93S0053	20-307-2431	Adaptor for probe filter element F-0,1GF150 Material SS 316.
90S2084	20-307-2323	Flange seal DN65 PN6 Graphit (67).
93S0011	20-307-2339	Thermostat (0-320°C), with over-temperature limiter and low-temperature alarm. for probe series SP.
93S0018	20-307-2340	Temperature resistant heat sink compound, 100g-tube.
93S0015	20-307-2341	Heating cartridge for SP2000-H, L=160mm, 230V/800W.
93S0017	20-336-1003	Heating cartridge for SP2000-H, L=160mm, 115VAC/800W.
93S0059	20-307-2342	PT100 sensor for SP2000H,,SP3200
93S0060	20-307-2385	Spare thermoelement Fe-CuNi for SP.../H320.
93S0061	20-336-1012	Spare thermocouple NiCr-Ni for SP.
93S0019	20-307-2344	Aluminium body for heating cartridge SP2000H.
93S0085	20-307-2386	Press-Screw M8 for filter housing lid SP2000/2100-H.
93S2125	20-307-2326	Clamp LK 115 for filter housing lid SP2000H.
93S0065	20-307-2345	Mounting clip 1 1/4" for heated sample line and SP2000-H.
93S2084	20-307-2329	Filter screw M6 for SP2000, 1.4571.
93S0090	20-307-2349	Hand screw M6 for SP2000 connection protection.
93S0070	20-307-2350	Spare weather protection shield for SP2000-H and SP2000-H/DIL.
93S4006	20-307-2427	Dilution cross 180°C/320°C empty, without any inserts Material SS316
93S4016	20-307-2430	Bypass T-piece 180°C/320°C empty, without any inserts Material SS316