

**Recommended Spare Parts**
**SP2500-H/C/I/BB-F 115V Gas Sample Probe**

| <b>Manufacturer P/N</b> | <b>Cemtrex P/N</b> | <b>Description</b>   |
|-------------------------|--------------------|--|
| 90S0020                 | 20-336-2000        | Filter element type S-2K150. Length: 150mm, material: ceramics, filter porosity: 2µm.              |
| 90F0125                 | 20-307-2314        | Filter element type F-0,1GF150. Length: 150mm, material: glass fiber, filter porosity: 0,1µm.      |
| 93S2083                 | 20-307-2315        | Special spun-glass hightemperature resistant for probes with /FW insert. Contents:1000g.           |
| 93S2096                 | 20-307-2316        | Spun glass cartridge element FW with Demister, stainless steel, without filling.                   |
| 93S0045                 | 20-336-5000        | Gasket (30) for filter element. Material: Viton.   |
| 93S0051                 | 20-307-2318        | Adaptor for probe filter element F-0,1GF150 Material PTFE.   |
| 93S0055                 | 20-307-2336        | Gasket (30) for filter element. Material: Graphite.  |
| 93S1000                 | 20-307-2381        | O-ring (68) for SP2500. SP2600 Material: Viton.  |
| 93S1005                 | 20-307-2382        | O-ring (86) for SP2500. SP2600 Material: Viton.  |
| 93S1010                 | 20-307-2383        | O-ring (105) for SP2500. SP2600 Material: Viton.   |
| 93S0030                 | 20-307-2337        | Gasket (69) for SP2000-H320. Material: Graphite.   |
| 90S2084                 | 20-307-2323        | Flange seal DN65 PN6 Graphit (67).   |
| 90S2077                 | 20-307-2322        | Flange gasket DN65 PN6B (67). Material: Novapress.   |
| 90S2075                 | 20-307-2324        | Flange gasket set for DN65 PN6B consisting of gasket (67) and a set of screws M12x60.              |
| 93S0010                 | 20-307-2338        | Thermostat (0-180°C), with over-temperature limiter and low-temperature alarm for probe series SP. |
| 93S0090                 | 20-307-2349        | Hand screw M6 for SP2000 connection protection.  |
| 93S0018                 | 20-307-2340        | Temperature resistant heat sink compound, 100g-tube.   |
| 93S0015                 | 20-307-2341        | Heating cartridge for SP2000-H, L=160mm, 230V/800W.  |
| 93S0017                 | 20-336-1003        | Heating cartridge for SP2000-H, L=160mm, 115VAC/800W.  |
| 93S0059                 | 20-307-2342        | PT100 sensor for SP2000H,,SP3200   |
| 93S0057                 | 20-307-2384        | Gasket 1 1/2" for filter element SP2500 Material: Novapress.                                       |
| 93S0060                 | 20-307-2385        | Spare thermoelement Fe-CuNi for SP.../H320.  |
| 93S0061                 | 20-336-1012        | Spare thermocouple NiCr-Ni for SP.   |
| 93S0019                 | 20-307-2344        | Aluminium body for heating cartridge SP2000H.  |
| 93S0085                 | 20-307-2386        | Press-Screw M8 for filter housing lid SP2000/2100-H.   |
| 93S2126                 | 20-307-2387        | Clamp LK for filter housing lid SP2500H/SP2600H  |
| 93S0065                 | 20-307-2345        | Mounting clip 1 1/4" for heated sample line and SP2000-H.  |

| <b>Manufacturer P/N</b> | <b>Centrex P/N</b> | <b>Description</b>   |
|-------------------------|--------------------|--|
| 93S2084                 | 20-3007-2329       | Filter screw M6 for SP2000, 1.4571.                            |
| 93S0070                 | 20-307-2350        | Spare weather protection shield for SP2000-H and SP2000-H/DIL. |
| 93S0075                 | 20-307-2351        | Weather protection shield for SP2000-H320 and SP2000-H320/DIL. |
| 02B1010                 | 20-307-2352        | Insert 4mm o.d. for PTFE hose 4/6mm, Material: SS316.          |
| 02B1020                 | 20-307-2353        | Insert 6mm o.d. for PTFE hose 6/8mm, Material: SS316.          |
| 93S0073                 | 20-307-2354        | Silicon cap SP2000H/210 sample out Material: Silicon grey.     |